


HERONLUX A2



GENERAL INFORMATION

SUPPLY VOLTAGE	220 - 240 V, 50-60 Hz
EFFICACY	108 lm/W
CCT	4000 K (natural white) on request 3000 K
CRI	80 on request 90
IP CLASS	IP20
APPLICATION HEIGHT	From 2 to 6 meters
BEAM ANGLE	55° on request 8° 15° 24° 38°
OPERATING TEMP.	-5 °C ~ +40 °C
STORAGE TEMP.	+5 °C ~ +50 °C
LIFETIME	L80B10 70 000 h (Ta 25°C)
INSTALLATION	recessed
CERTIFICATION	CE and RoHS Compliant
OPTIONAL FEATURES	DALI
WARRANTY	5 years

LIGHT DISTRIBUTION GRAPHS



ITEM DESCRIPTION

Recessed luminaire for professional lighting. Due to its versatility, HeronLux luminaires are perfect to illuminate such spaces as corridors, shopping centers, hallways and etc.

ENVIRONMENT

- Offices
- Shopping malls
- Hotel halls
- Conference rooms
- Corridors
- Schools
- Hospitals

FEATURES & BENEFITS

- Easy installation
- 5 years warranty

REFLECTOR COLOUR



white



black

*on request: chrome, silver, chrome black, gold

ORDERING INFORMATION

SKU	HOUSING COLOUR	REFLECTOR COLOUR	BEAM ANGLE	POWER	LUMEN OUTPUT	CCT	OPTIONAL FEATURES
BDNP-T2-WW-55840118	white	white	55°	18 W	1951 lm	4000K	ON-OFF
BDNP-T2-WW-55840118-DA	white	white	55°	18 W	1951 lm	4000K	DALI
BDNP-T2-WB-55840118	white	black	55°	18 W	1951 lm	4000K	ON-OFF
BDNP-T2-WB-55840118-DA	white	black	55°	18 W	1951 lm	4000K	DALI