

HERONLUX A5



ITEM DESCRIPTION

Surface-mounted luminaire for professional lighting. Due to its versatility, HeronLux luminaires are perfect to illuminate such spaces as corridors, shopping centers, hallways and etc.

ENVIRONMENT

- Offices
- Shopping malls
- Hotel halls
- Conference rooms
- Corridors
- Schools
- Hospitals


FEATURES & BENEFITS

- Easy installation
- 5 years warranty

GENERAL INFORMATION


SUPPLY VOLTAGE	220 - 240 V, 50-60 Hz
EFFICACY	124 lm/W
CCT	4000 K (natural white) <i>on request 3000 K</i>
CRI	80 <i>on request 90</i>
IP CLASS	IP20
APPLICATION HEIGHT	From 2 to 6 meters
BEAM	60° <i>on request 15° 30°</i>
OPERATING TEMP.	-5 °C ~ +40 °C
STORAGE TEMP.	+5 °C ~ +50 °C
LIFETIME	L80B10 70 000 h (Ta 25°C)
INSTALLATION	surface
CERTIFICATION	CE and RoHS Compliant
OPTIONAL FEATURES	DALI
WARRANTY	5 years

LIGHT DISTRIBUTION GRAPHS



— C0-180 — C90-270 45°

REFLECTOR COLOUR



white



black

**on request: silver, rose gold, gold*

ORDERING INFORMATION

SKU	HOUSING COLOUR	REFLECTOR COLOUR	BEAM ANGLE	POWER	LUMEN OUTPUT	CCT	OPTIONAL FEATURES
BDNP-SM-WW-45840I20	white	white	45°	20 W	2483 lm	4000K	ON-OFF
BDNP-SM-WW-45840I20-DA	white	white	45°	20 W	2483 lm	4000K	DALI
BDNP-SM-WB-45840I20	white	black	45°	20 W	2483 lm	4000K	ON-OFF
BDNP-SM-WB-45840I20-DA	white	black	45°	20 W	2483 lm	4000K	DALI