

EVACUATION LIGHTING OPTIONS



GENERAL INFORMATION

SUPPLY VOLTAGE	230V; 50Hz
OPERATING TEMP.	+10 °C ~ +55 °C
INSTALLATION OPTIONS	Surface / Wall / Suspended
CERTIFICATION	CE



BEMP-EV-T1-EXIT-WM BEMP-EV-T1-GC-WM BEMP-EV-T2-EXIT-WM BEMP-EV-T2-GC-WM BEMP-EV-T5-EXIT-WM

WALL MOUNTED MODULE

SKU	IP	TEST*	EMERGENCY AUTONOMY	POWER CONSUMPTION, W (while charging)	VISIBILITY	DIMENSIONS, MM
BEMP-EV-T1-EXIT-WM	65	manual	1 h	1.5	24 m	269x144x42
BEMP-EV-T1-GC-WM	65	manual	1 h	1.5	24 m	269x144x42
BEMP-EV-T2-EXIT-WM	65	manual	3 h	4	20 m	352x110x73
BEMP-EV-T2-GC-WM	65	manual	3 h	4	20 m	352x110x73
BEMP-EV-T5-EXIT-WM	44	manual	3 h	1	25 m	299x206x43

*might be auto-test upon request

Legend

EXIT – evacuation sign

GC - fire hose sign



BEMP-EV-T1-EXIT-SM BEMP-EV-T2-EXIT-SM BEMP-EV-T5-EXIT-SM

CEILING MOUNTED MODULE

SKU	IP	TEST*	EMERGENCY AUTONOMY	POWER CONSUMPTION, W (while charging)	VISIBILITY	DIMENSIONS, MM
BEMP-EV-T1-EXIT-SM	65	manual	1 h	1.5	24 m	269x144x42
BEMP-EV-T2-EXIT-SM	65	manual	3 h	3.5	30 m	352x232x110
BEMP-EV-T5-EXIT-SM	44	manual	3 h	1	25 m	299x206x43

*might be auto-test upon request



BEMP-EV-T1-EXIT-SP BEMP-EV-T2-EXIT-SP BEMP-EV-T5-EXIT-SP

SUSPENDED MODULE

SKU	IP	TEST*	EMERGENCY AUTONOMY	POWER CONSUMPTION, W (while charging)	VISIBILITY	DIMENSIONS, MM
BEMP-EV-T1-EXIT-SP	65	manual	1 h	1.5	24 m	269x144x42
BEMP-EV-T2-EXIT-SP	65	manual	3 h	3.5	30 m	352x232x110
BEMP-EV-T5-EXIT-SP	44	manual	3 h	1	25 m	299x206x43

*might be auto-test upon request